



VGA Splitter
VSA-108
VSA-116

Video Splitters, **VSA-108** and **VSA-116** broadcast and boost one VGA signal source for 8 or 16 VGA monitors. There is no software or interface card to install. Simply connect the cables, power up the system and you are ready to duplicate VGA images to multiple monitors with excellent clarity. Superb high bandwidth circuit enables a high-resolution VGA signal of 350 MHz to be displayed on multiple monitors.

With the mountable size, **VSA-108** and **VSA-116** can be easily mounted on the rack for space saving and working efficiently.

Features

- ↳ Duplicate one VGA input to multiple VGA outputs.
- ↳ Effective transmission distance is 65M (210ft) with UL-2919 rated VGA cables
- ↳ Automatic power-save when VGA input is lost
- ↳ Applicable to VGA, SVGA and multi-sync monitors
- ↳ Cascaded operation for increased VGA outputs
- ↳ Crisp clear VGA images
- ↳ Rack mountable

Specifications

	VSA-108	VSA-116
Number of VGA output	8	16
Signal bandwidth	350MHz	
Signal type	VGA, SVGA, Multi-sync	
LED indicators	POWER (green) x 1 ACTIVE (amber) x 1	
Cable length	65M (210ft) Max.	
Connector	Input	HDB15 male x 1
	Output	HDB15 female x 8 HDB15 female x 16
Power consumption	DC 9V, 200mA, normal operation 10mA, power-save mode	
Enclosure	Metal	
Weight (g)	1534	1675
Dimensions H x W x D (mm)	43 x 438 x 125	

Connection Pattern

